

3M™ Scotchkote™ Electrical Coating

Data Sheet

June 2011

Description 3M™ Scotchkote™ Electrical Coating is designed as a fast-drying sealant and bonding agent intended for use on joints wrapped with plastic electrical tape.

- Features**
- Compatible with Scotch® Vinyl Electrical Tapes
 - Fast Drying
 - Flexible when dry
 - Self-contained applicator
 - No waste if container resealed after use

Applications This coating is intended for use as an outer seal on vinyl tape applications which are subjected to excessive amounts of oil. It is designed to help improve the weather resistance of the taped joint of splice. It is suitable for direct burial, direct water immersion or above ground applications. Contact with potable water is not recommended.

Precautionary and first aid information for this product may be found in its Material Safety Data Sheet and on the product container.

Typical Properties Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73°F (23°C) unless otherwise stated.

Physical Properties	Typical Value
Tack Free Time 72°F (22°C)	15 mins.
Adhesion to: Wood Metal Rubber Plastic	Good Good Good Good

Electrical Properties (Test Method)	Typical Value
Dielectric Strength Dry 24 hrs. in H ₂ O	450 volts/mil 200 volts/mil

3M™ Scotchkote™ Electrical Coating

Typical Properties, continued

Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73°F (23°C) unless otherwise stated.

Chemical Properties	Typical Value
Solvent	Acetone, Methyl Ethyl Ketone, Toluene
Solids (25%)	Synthetic rubber & resin
Flash Point	0°F (-18°C) (closed cup)

Installation Techniques

After taping splices with Scotch® Vinyl Electrical Tape, apply 3M™ Scotchkote™ Electrical Coating evenly over splice, extending a short distance onto the cable insulation. Be sure the surface is clean, dry and free from oil or grease before electrical coating is applied.

Shelf Life & Storage

This product has a 2-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

Availability

Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1.800.245.3573.

Not for sale in these states:

California, Connecticut, district of Columbia, Delaware, Illinois, Indiana, Maine, Maryland, Massachusetts, Michigan, New Hampshire, New Jersey, New York, Ohio, Pennsylvania, Rhode Island and Virginia.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M, Scotch and Scotchkote are trademarks of 3M Company.

**Electrical Markets Division**

6801 River Place Blvd.
Austin, TX 78726-9000
800.245.3573
FAX: 800.245.0329
www.3M.com/electrical

Please recycle
© 3M 2011 All rights reserved
78-8131-7577-1 B