

tasker®

Braided shielded cables sect. 0,75 mm²



FirestoP®



Applications:
Braided shielded cables for data transmission and electronics.

Characteristics:
Conductors: stranded in O.F.C. red copper
Cond. Insulation: Flame Retardant
PVC CEI 20-22/II°
Core colours: Brown, Blue, Black, Yellow/green, Red, White, Yellow, Grey, Bright-orange, Green, Violet, Pink
Total Shield: Braided covering 85% O.F.C. red copper
External Sheath: Flame Retardant
PVC CEI 20-22/II°
Sheath colour: Black



Max rated Voltage AC: 49 V.
Operative Temperature °C.: -15° / +70°

tasker® Code	Cond. number	Nominal section mm ²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C 1075	1	1 x 0,75 (18 AWG)	24x0,20	2,3		4,0	100	B	2,6
C 2075	2	2 x 0,75 (18 AWG)	24x0,20	2,3		6,4	100	B	5,8
C 3075	3	3 x 0,75 (18 AWG)	24x0,20	2,3		6,8	100	B	7,8
C 4075	4	4 x 0,75 (18 AWG)	24x0,20	2,3		7,4	100	B	11,0
C 5075	5	5 x 0,75 (18 AWG)	24x0,20	2,3		7,8	100	B	9,0
C 6075	6	6 x 0,75 (18 AWG)	24x0,20	2,3		8,6	100	B	12,0
C 8075	8	8 x 0,75 (18 AWG)	24x0,20	2,3		10,6	100	B	14,5
C10075	10	10 x 0,75 (18 AWG))	24x0,20	2,3		11,2	100	B	15,0
C12075	12	12 x 0,75 (18 AWG)	24x0,20	2,3		11,6	100	B	25,0

Conductor Resistance	Capacity Core/core	Capacity Core/shield
Ω/Km ± 5%	pF/mt	pF/mt
30		260
30	170	300
30	150	270
30	140	260
30	140	260
30	130	250
30	110	220
30	100	210
30	100	200