

JZC-22F-1Z 10A SPECIFICATION

COIL DATA

coil rated voltage (V)	coil resistance at 25° C (Ω)	pick-up voltage (max) at 25°C	drop-out voltage (min) at 25°C	operate time (ms)	release time (ms)
6v DC	100±10%	75% of rated voltage	10% of rated voltage	10	5
12VDC	400±10%				
24VDC	1600±10%				
48VDC	6400±10%				

CHARACTERISTICS

Outline dimension (mm)	: 22.5x16x16.5 (L*W*H)
Contact form	: 1Z (SPDT)
Contact rating (Resistive)	: 10A 250VAC
Power consumption	: DC≤0.45W
Contact resistance	: 100MΩ MAX
Insulation resistance	: 100MΩMin (DC500V)
Dielectric strenght	: Between open contant: 500VAC, 1 minute
	: Between contact and coil: 1500VAC, 1 minute
Vibration resistance	: 10~55Hz amplitude 1.0 mm
Shock resistance	: Damage limits: 100G, operating extremes: 10G
Ambient tempetature	: -30° C ~ +60°C
Life expectancy for mechanical	: 10,000,000 operations
Life expectancy for electrical	: 100,000 operations
Terminal type	: PCB
Weight	: Approx.11g