


MALE PROTECTION CAP

R141.802.000

Series : BNC



All dimensions are in mm.



COMPONENTS

MATERIALS

PLATING (µm)

BODY
 CENTER CONTACT
 OUTER CONTACT
 INSULATOR
 GASKET
 OTHERS PARTS
 -
 -

BRASS
 -
 -
 -
 SILICONE RUBBER
 -
 -
 -

NICKEL 2
 -
 -
 -
 -
 -

MALE PROTECTION CAP

R141.802.000

Series : BNC

PACKAGINGSPECIFICATION

QAE 06-02 - -

Standard	Unit	Other
100	'W' option	Contact us

ELECTRICAL CHARACTERISTICSENVIRONMENTAL

Impedance	50 Ω
Frequency	NA GHz
VSWR	NA + 0,0000 x F(GHz) Maxi
Insertion loss	NA $\sqrt{F(\text{GHz})}$ dB Maxi
RF leakage	NA - F(GHz) dB Maxi
Voltage rating	NA V eff Maxi
Dielectric withstanding voltage	NA V eff mini
Insulation resistance	NA M Ω mini

Operating temperature	-65/+165 °C
Hermetic seal	NA Atm.cm ³ /s
Panel leakage	NA

OTHER CHARACTERISTICS

Assembly instruction

Others :

MECHANICAL CHARACTERISTICS

Center contact retention	
Axial force - Mating end	NA N mini
Axial force - Opposite end	NA N mini
Torque	NA N.cm mini

Recommended torque	
Mating	NA N.cm
Panel nut	NA N.cm

Mating life	500 Cycles mini
Weight	6,5000 g