

Sheathed cables



Applications:
Flexible sheathed cables for wiring and electronics.

Characteristics:
Conductors: stranded in O.F.C. red copper
Cond. insulation: PVC
Core colours: Brown, Blue, Black, Yellow/green, Red, White, Yellow, Grey, Bright-orange, Green, Violet, Pink, White/red, White/black, White/blue, White/green, White/brown, White/yellow, White/violet, Blue/red, Blue/black, Blue/green, Blue/brown, Blue/yellow
External Sheath: PVC
Sheath colour: Black

tasker® Code	Cond. number	Nominal section mm²	Cond. Format. mm.	External Core Ø mm.	External Inner Sheath Ø mm.	External Cable Diameter mm.	Reel or Spool (* pag. II)		
							mt.	Type	Kg.
C158	6	6 x 0,25 (23 AWG)	8x0,20	1,4		5,3	100	B	4,5
C159	12	12 x 0,25 (23 AWG)	8x0,20	1,4		7,0	100	B	7,5
C160	16	16 x 0,25 (23 AWG)	8x0,20	1,4		8,0	100	B	10,0
C161	24	24 x 0,25 (23 AWG)	8x0,20	1,4		9,8	100	B	14,5

Conductor Resistance	Max rated Voltage	Operative Temperature
Ω/Km ± 5%	AC - V	°C
75	49	-15 / +70
75	49	-15 / +70
75	49	-15 / +70
75	49	-15 / +70