

Technical Datasheet

tasker® C133 – 1x0,28 mm²

Flexible Unipolar Cable



CATEGORY Unipolar Cable (See Electronic Catalogue)

APPLICATIONS Electronics and wiring

A: Soft **PVC** Sheath. Available in different color.
Outer cable Diam. Ø 1,20 (±0,10) mm.

B: O.F.C. Red Copper Stiff Wire formation 1x0,60 mm.
Nom. Cross section 1x0,28 mm².

MARKING not marked

CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,

PRODUCTION or Metallic Armored.

Cable Properties

Conductor Resistance	67,00 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			