



SPINE CON PORTAFUSIBILE

IEC power inlets fused | *Prises mâles avec porte-fusible*

Tensione 250 V	Voltage 250 V	Tension 250 V
Corrente 10 A	Current 10 A	Courant 10 A
Contatti Ottone stagnato	Contacts Tinned brass	Contacts Laiton étamé
Corpo Nylon UL94-V0	Body Nylon UL94-V0	Corps Nylon UL94-V0
Norme riferimento EN60320-1	Standards EN60320-1	Normes EN60320-1
Cod. omologazione Bulgin PF0001 - PF0011	Approval code Bulgin PF0001 - PF0011	Code d'homologation Bulgin PF0001 - PF0011



Codice Code Code	Spessore pannello Panel thickness Épaisseur du panneau	Contatti Contacts Contacts	DIM "A"
Fissaggio Snap-In Snap-In fixing Fixation à enclenchement			
PX6111028	1	2,8	27
PX6111528	1,5	2,8	27
PX6112028	2	2,8	27
PX6113028	3	2,8	27
PX6111063	1	6,3	28,6
PX6111563	1,5	6,3	28,6
PX6112063	2	6,3	28,6
PX6113063	3	6,3	28,6
Fissaggio a vite orizzontale Horizontal screw fixing Fixation horizontale à vis			
PX6010028	—	2,8	27,0
PX6010063	—	6,3	28,6

