THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP. NOTES, UNLESS OTHERWISE SPECIFIED: ROHS COMPLIANT. WEIGHT/PC INSTALLS \* THE FOLLOWING PANDUIT CABLE TIE CROSS-SECTION \*\* TOOL NO. \* THIS TOOL TIGHTENS CABLE TIES AND CUTS ΟZ GRAMS OFF EXCESS PORTION WHEN PRESET TENSION SM,M,I,S IS ATTAINED. GS2B-E 13.55 385 \*\* CABLE TIE CROSS-SECTION CODE: SM = SUB-MINIATURE M = MINIATURE I = INTERMEDIATE S = STANDARD. TENSION ADJUSTMENT KNOB -DIMENSIONS IN BRACKETS ARE METRIC. 1.28 32.43 TENSION SETTING WINDOW -- .57 TENSION SETTING LABEL -14.56 .75 — BLADE GUARD WIDTH [19.13] BLADE GUARD HE I GHT - .055/.065 BLADE GUARD -[1.40/1.65] 5.71 [145.07] OVERALL HE I GHT — 2.60 — [66.09] .94 [23.76] — - 7.82 [198.63] Α CD, GS2B-E Customer/Military Drawing **TENSION SETTINGS** R27576AA/01 TIE WIDTH R27576AA\_DS\_WB27576B01/01A S-MIN MIN STD INT UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [ mm ] SETTING 0-1 1-3 3-5 5-8 .x ± .1 [2.54] .xxx ± .005 [ .127] 8-26-15 JEH ABJ ABF ADDED TENSION SETTING VIEW 4850 .xx ± .01 [ .25] ANGLES ± 5 ° DRAWING NUMBER: THIRD ANGLE PROJECTION 00 ABJ ABJ RELEASED 4769 1-26-15 JEH WB27576B01 CHK APR REV DATE BY DESCRIPTION ECN JEH 1-26-15 ABJ 1:2 SHT 1 0F 1