

## Part No.:Hi-05A3YGDAC-211

**19/04305-00**

§ Standard 5mm diameter package.

### Characters

§ High intensity.

ITEM		MATERIALS
Resin(Mold)		Epoxy
Lens Color Code	C	Water Transparent
	T	Colored Transparent
	D	White Diffused
	E	Colored Diffused
Lead Frame		Ag Plating Iron Alloy
Dice		InGaN

### Absolute Maximum Ratings ( Ta=25°C )


Item	Symbol	Value	Unit
Power Dissipation	PD	100	mW
DC Forward Current	IF	30	mA
Pulsed Forward Current	IFP	100*	mA
Reverse Voltage	VR	5	V
Operating Temperature	Topr	-25 ~ +80	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Soldering Temperature	Tsol	260for5sec△	°C

\* Duty 1/10 Pulse Width 0.1ms    △ At the position of 4mm from the bottom of the package

### Electrical-Optical Characteristics ( Ta=25°C )

Parameter	Symbol	Value			Unit	Test condition
		Min.	Typ.	Max.		
Forward Voltage	Vf	---	2.1	2.4	V	If=20mA
Luminous intensity	Iv	750	1200	2000	mcd	If=20mA
Wavelength	X(&λd)	---	590	595	(nm)	If=20mA
	y	---	---	---	---	If=20mA
Reverse Current	Ir	---	---	5	μA	Vr=5V
Viewing angle	2θ1/2	---	15	---	Deg	If=20mA
Spectral half bandwidth	Δλ	---	25	---	nm	If=20mA

### Outline Dimensions



§ All dimensions are in millimeters ( inches ).

§ Tolerance is ±0.25 (.010) mm unless otherwise noted.

### Directive Characteristics ( Ta=25°C )

