

Datasheet

Stock No: 145-0626, 145-0627, 145-0628, 145-0629





Key Switch Complete Unit



Specifications:

- 22mm Diameter
- Sprung return head options available
- IP65 rated
- Complete unit with built-in contact block
- Conformity with RoHs directive

RS Stock No		145-0626	145-0627	145-0628	145-0629
Characteristics					
Type		Key Switch			
Mounting Diameter		22mm			
Colour		Black			
Contact		1NO + 1NC			
Number of Positions		2 Position		3 Position	
Sprung Return		None	From right	None	From left and right
Function		Selector			
Type		Non Illuminated			
Weight		20g			
Mounting		Fixing hole: Ø 22.5 mm			
Fixing Centre		Locking nut beneath head			
Terminal Torque		0.8 Nm			
Contact Type		Make & Break			
Mechanical Life		0.5 million cycles			
Electrical Life of Contact		0.5 million cycles			
Utilization Category	Supply	IEC-60947-5-1	UL-508		ITH/Thermal Current
	AC	AC-15	A600		10A
	DC	DC-13	P300		
Rated Voltage and Current	230Vac	6A			
	120Vac	6A			
	24Vdc	1.5A			
Current Carrying Material		Brass			
Contact Material		AgNi			
Housing Material		Nylon FR			
Operating Temperature		-25°C to 65°C			
Storage Temperature		-30°C to 70°C			
Hv Test for 60 sec		2.5KV (All Terminal Shorted Together)			
Insulation Resistance at 500 VDC		50 M Ohm			
Contact Resistance		20 M Ohm			
MV drop at 16 A DC		200 MV			

IP Rating	IP65 above panel (As per IEC/EN -60529) & IP20 for Terminals NEMA 1
Certification	   
<p>Product Drawing</p> 