

PMC-1401



PMC-1401

Standard Reed Switch

Electrical Characteristics		@ 25 °C
Contact form		A
Contact material		Ru
Contact rating max.	W / VA	10
Switching voltage max.	VDC	200
	VAC	140
Switching current max.	A	1
Carry current max.	A	1.2
Breakdown voltage min.	VDC	240
Contact resistance max. (initial)	mΩ	100
Insulation resistance min.	Ω	10 ¹⁰

Features
➤ Form A switch (normally open type) ➤ Most cost-efficient general purpose Reed Switch ➤ Standard size with 14 mm glass length ➤ Various sensitivity ranges available

Magnetical Characteristics (of unmodified Reed Switch)		@ 25 °C
Pull in range available	AT	10 - 30
Drop out min.	AT	4
Test coil	TC	014
Test equipment tolerance	± AT	2

Operating Characteristics		@ 25 °C
Switching frequency max.	Hz	500
Resonant frequency typ.	Hz	4000
Operate time max. (incl. bounce)	ms	1
Release time max.	ms	0.4

Environmental Characteristics		
Operating temperature	°C	-60 to +155
Vibration (50-2000 Hz)	g	20
Shock (1/2 sin 11 ms)	g	100

Life Expectancy			
Resistive load	Voltage	Current	Operations
	12 VDC	0,1 A	2 x 10 ⁸
	24 VDC	0,4 A	5 x 10 ⁷

Ordering Information	
Packing Unit	1500 pcs
Weight per piece	0.14 g
Weight per package	270 g
Standard AT ranges	
	10 to 15 AT
	15 to 20 AT
	20 to 25 AT
	25 to 30 AT

Dimensions in mm	

Ordering example
PMC-14011015 describes PMC-1401 with 10 to 15 AT.