

Technical Datasheet

tasker® C160 – 16x0,25 mm²

Flexible Multi Conductor Cable

✓
RoHS₂
2002/95/EC
2011/65/UE



NOTE

CATEGORY

APPLICATIONS

The picture does not represent the real number of conductors.
Multi Conductor Cable (See Electronics Catalogue)
wiring and electronics

- A:** Black Soft **PVC** Sheath.
Outer Diam. Ø 8,00 (±0,10) mm.
- B:** Cores Insulation with Soft **PVC** sheaths.
DIN 47100 Standards – White, Brown, Green, Yellow, Grey, Pink,
Blue, Red, Black, Violet, Grey/Pink, Red/Blue, White/Green, Brown/Green,
White/Yellow, Yellow/Brown.
Diam. Ø 1,40 (±0,20) mm.
- C:** Stranded O.F.C. Red Copper formation 8x0,20 mm.
Nom. Cross section 16x0,25 mm².

MARKING

CUSTOM

PRODUCTION

tasker® C 160 SHEATHED CABLE ITALY
This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
or Metallic Armored.

Cable Properties

Conductor Resistance	75,85 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio
Impiego		Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 26.05.17