

Technical Datasheet

tasker® C161 – 24x0,25 mm²

Flexible Multi Conductor Cable


RoHS₂
 2002/95/EC
 2011/65/UE



NOTE

CATEGORY

APPLICATIONS

The picture does not represent the real number of conductors.
 Multi Conductor Cable (See Electronics Catalogue)
 wiring and electronics

- A:** Black Soft **PVC** Sheath.
 Outer Diam. Ø 9,80 (±0,10) mm.
- B:** Cores Insulation with Soft **PVC** sheaths.
 DIN 47100 Standards – White, Brown, Green, Yellow, Grey, Pink,
 Blue, Red, Black, Violet, Grey/Pink, Red./Blue, White/Green, Brown/Green,
 White/Yellow, Yellow/Brown, White/Grey, Grey/Brown, White/Pink,
 Pink/Brown, White/Blue, Brown/Blue, White/Red, Brown/ Red.
 Diam. Ø 1,40 (±0,20) mm.
- C:** Stranded O.F.C. Red Copper formation 8x0,20 mm.
 Nom. Cross section 24x0,25 mm².

MARKING

CUSTOM

PRODUCTION

tasker® C 161 SHEATHED CABLE ITALY
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
 or Metallic Armored.

Cable Properties

Conductor Resistance	75,85 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			