



- 1.CABLE:NO UL.,28AWG(7/0.127),TINNED AND STRANDED COPPER WIRE
 INSULATOR:PVC,ID:0.85mm ,CABLING:9C+DRAIN WIRE
 SHIELD:AL/MY COVERAGE
 JACKET:PVC,COMPLIANCE ROHS,COLOR:BEIGE,D.D:5mm
 2.2PCS CONNECTOR:DB-SUB 9 WAYS FEMALE SOLDER TYPE CONNECTOR
 INSULATOR:P.B.T.+GLASS FIBER,COLOR:BLUE
 CONTACT: COPPER ALLOY,GOLD FLASH OVER NICKEL PLATED
 SHELL:NICKEL PLATED,
 CONNECTOR COMPLIANCE ROHS
 3.HOOD:PVC MOLDED TYPE WITH FOIL SHIELDED ON INNER
 ON INNER MOLD AND INJECTION OUTER MOLD WITH
 THUMB SCREW#4-40 UNC
 COLOR:BEIGE,COMPLIANCE ROHS
 4 Fulfill ROHS Guideline
 5.ELECTRONIC TEST:100% OPEN SHORT+MISS WIRE TEST

PIN OUT

DB9PIN FEMALE(J1)	WIRE	DB9PIN FEMALE(J2)
1	_____	1
2	_____	2
3	_____	3
4	_____	4
5	_____	5
6	_____	6
7	_____	7
8	_____	8
9	_____	9
SHELL	DRAIN WIRE	SHELL

PART NO CAB-09GG/10

SHEET NO 1

THIRD ANGLE PROJECTION

TITLE: DB9 PIN FEMALE TO DB9 PIN FEMALE
 BEIGE COLOR,L10M

SCALE N.T.S DRAWN BY & DATE

SIZE A4 CHECKED BY & DATE

UNIT APPROVED BY & DATE

☒ mm ☐ INCH

DWN NO D-CAB-09GG/10

