

LogiLink®



Carbon Monoxide Detector With LCD Display

Art. No.: SC0123



Complies with
EN 50291-1
Standard



Built-in 10 Years
DC 3 V lithium battery



Make Your Home Safer

- Designed to give the earliest possible warning of dangerous carbon monoxide (CO) leaks in the surrounding air, with loud acoustic alarm signal and rapid flashing LED indication.



85dB Alarm



LCD Display



LED Indicator



Low Battery Warning



Easy to Install



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



SC0123



4 052792 074840

Made in China



Highly Accurate & Responsive

Features electrochemical technology quickly respond to toxic gas leaks. With an 85 dB alarm and flashing LED indicator, the alarm provide early warning to avoid dangerous accidents.

10 Years Sensor and Battery

Advanced sensor with up to 10 years lifespan. Built-in 3 V lithium battery, which could keep for 10 years without replacing to protect environment.

Guaranteed Quality

This carbon monoxide detector complies with the EN EN 50291-1 standard, ensuring high quality and durability for home safety.

Protects Your Family

Place the carbon monoxide detector anywhere you want to enhance the safety of your family; watches over you around the clock.



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.




SC0123



Made in China

Recommended Installation Location:

- Install the detector on walls, at least 1.8 m above the ground, outside sleeping areas, kitchen, garages or rooms with fireplaces—not in the basement.
- Keep 1–3 m away from flame-producing appliance such as a stove, grill or fireplace, and avoid areas with poor ventilation, strong winds, or high humidity.



Specifications:

Power	DC 3V CR123A battery
Sensor Type	Electrochemical
Standard	EN 50291-1:2018+AC:2021
Standby Current	<20 uA
Alarm Current	<45 mA
Alarm Volume	≥85 dB@3 m
Alarm Status	When CO concentration is 30 ppm, no alarm within 120 minutes When CO concentration is 50 ppm, alarm within 60–90 minutes When CO concentration is 100 ppm, alarm within 10–40 minutes When CO concentration is 300 ppm, alarm within 3 minutes
CO Detect Range	0–999 ppm
Sensor Life	10 years
Battery Life	10 years
LCD Display	Battery, CO ppm, Fault/Alarm
LED Indicator	Green: Power; Red: Alarm; Yellow: Fault
Button	Test button
Mounting Methods	Fasten by screws or 3M pad
Housing Material	PC + ABS
Color	White
Operating Temperature	-10–40°C
Operating Humidity	0–95% RH (non-condensing)
Dimensions	8.65 x 8.65 x 3.05 cm
Weight	124.2 g

Package Contents:

- » 1x Carbon Monoxide Detector
- » 2x Screws
- » 2x Plastic Dowels
- » 1x 3M Carpet Pad
- » 1x User Manual

Package Information:

- » Packing Dimension: 90 x 40 x 95 mm
- » Packing Weight: 0.154 kg
- » Carton Dimension: 470 x 430 x 210 mm
- » Carton Q'ty: 100 pcs
- » Carton Weight: 15.4 kg



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.



SC0123



4 052792 074840

Made in China