



Part No.:Hi-05D3SYT-169W2


19/04275-00

§ Standard 5mm diameter package.

Characters

§ High intensity.

ITEM	MATERIALS	
Resin(Mold)	Epoxy	
Lens Color Code	C	Water Transparent
	T	Colored Transparent
	D	White Diffused
	E	Colored Diffused
Lead Frame	Ag Plating Iron Alloy	
Dice	GaInP	


Outline Dimensions

§ All dimensions are in millimeters (inches) .

§ Tolerance is ± 0.25 (.010)mm unless otherwise noted.**Absolute Maximum Ratings (Ta=25°C)**

Item	Symbol	Value	Unit
Power Dissipation	PD	100	mW
DC Forward Current	IF	30	mA
Pulsed Forward Current	IFP	100	mA
Reverse Voltage	VR	5	V
Operating Temperature	Topr	-25 ~ +80	°C
Storage Temperature	Tstg	-40 ~ +100	°C
Soldering Temperature	Tsol	260for5sec	°C

* Duty 1/10 Pulse Width 0.1ms ▲ At the position of 4mm from the bottom of the package

Directive Characteristics (Ta=25°C)**Electrical-Optical Characteristics (Ta=25°C)**

Parameter	Symbol	Value			Unit	Test condition
		Min.	Typ.	Max.		
Forward Voltage	Vf	---	1.8	2.4	V	If=20mA
Luminous intensity	Iv	10	20	40	mcd	If=20mA
Wavelength	X(λd)	585	590	595	(nm)	If=20mA
	y	---	---	---	---	If=20mA
Reverse Current	Ir	---	---	5	μA	Vr=5V
Viewing angle	2θ1/2	---	120	---	Deg	If=20mA
Spectral half bandwidth	Δλ	---	25	---	nm	If=20mA