

## Professional connectors COAX TV Video 75 Ω



**SP 71**  
Cable Ø: mm. 8,0  
Soldering type

## F Video 75 Ω



**SP 72**  
Cable Ø: mm. 8,0  
Soldering type

## F Video 75 Ω



**SP 73**  
Cable Ø: mm. 8,0  
Soldering type

## SCART Audio Video

### COMPACT



**SP 69**  
Cable Ø: mm. 11,0  
Soldering type

### tasker® SP 71

Coaxial TV connector (female)

- Characteristics:**  
**Impedance:** 75 Ω  
**Shell:** Ergonomic in Anodized Metal Anti-Oxidant  
**Applicable Cable Diameter:** Max. Ø mm. 8,0  
**Sheath arrester:** Inner with serrated jaws  
**Clutches:** Gold Plated 24 K - 1,5 μ  
**Insulation:** Plastic Steel resistant up to 120°C. and anti-aging Gold Plated 24 K - 1,5 μ  
**Inner Contacts:** Soldering type  
**Colour:** Red  
**Packaging:** Multiple of n° 10 pieces

### tasker® SP 72

Professional F connector

- Characteristics:**  
**Impedance:** 75 Ω  
**Shell:** Ergonomic in Anodized Metal Anti-Oxidant  
**Applicable Cable Diameter:** Max. Ø mm. 8,0  
**Connection lock:** Round threaded ferrule for manual lock  
**Sheath arrester:** Inner with serrated jaws  
**Clutches:** Gold Plated 24 K - 1,5 μ  
**Insulation:** Plastic Steel resistant up to 120°C. and anti-aging Gold Plated 24 K - 1,5 μ  
**Inner Contacts:** Soldering type  
**Colour:** Red  
**Packaging:** Multiple of n° 10 pieces

### tasker® SP 73

Professional F connector

- Characteristics:**  
**Impedance:** 75 Ω  
**Shell:** Ergonomic in Anodized Metal Anti-Oxidant  
**Applicable Cable Diameter:** Max. Ø mm. 8,0  
**Connection lock:** Exagonal threaded nut for key lock  
**Sheath arrester:** Inner with serrated jaws  
**Clutches:** Gold Plated 24 K - 1,5 μ  
**Insulation:** Plastic Steel resistant up to 120°C. and anti-aging Gold Plated 24 K - 1,5 μ  
**Inner Contacts:** Soldering type  
**Colour:** Red  
**Packaging:** Multiple of n° 10 pieces

### tasker® SP 69

Professional SCART Connector

#### COMPACT

- Characteristics:**  
**Shell:** Ergonomic in printed and glazed brass Anti-Oxidant  
**Applicable Cable Diameter:** Max. Ø mm. 11,0  
**Sheath arrester:** Threaded nut in printed brass  
**Clutches:** Gold Plated 24 K - 1,5 μ  
**Insulation:** Plastic Steel resistant up to 120°C. and anti-aging Gold Plated 24 K - 1,5 μ  
**Inner Contacts:** Soldering type  
**Colour:** Glazed Chrome  
**Packaging:** Multiple of n° 10 pieces